

### FEATURES

### WARWICK, QUEENSLAND

Marblestone is a screened multi-coloured limestone in either 16mm, 30mm or 50mm size range and colour consistency cannot be guaranteed.

Marblestone is produced from limestone as quarried at Warwick and are processed under our quality assurance program producing consistent chemical and physical properties resulting in a predictable and repeatable product performance for our customers. Terrequip Australia actively manages a Quality Management System certified to ISO9001:2008.

Marblestone is used for landscaping and drainage work, as an aggregate in concrete or for paths and driveways. In industrial applications marblestone can be used for acid neutralisation. The following typical properties may help you to determine the suitability of the product to best suit your application.

Warwick Marblestone 03/12

### PARTICLE SIZE ANALYSIS

Mean Values. These Do Not Represent A Specification

	Mesh Size		50-20mm	30-10mm	16mm
	mm	BSS			
Typical Mean % Retained on Individual Sieves	53		0.0		
	40		19.9		
	35.5		24.3		
	28		34.7	0.7	
	25		-	11.3	
	19		20.2	29.7	
	16			12.3	1.4
	13.2			-	28.1
	9.5			40.3	42.6
	5				25.9
	Pan			0.7	5.7

### ORDERING INFORMATION

Shipping Point:

Warwick, Queensland

Availability:

Bulk

**Disclaimer:** This Technical Information Sheet is provided for general information purposes only. Ranges and values of trial sample testing or on a Technical Information Sheet are typical or expected ranges and are not guaranteed ranges. Terrequip Australia makes no warranties express or implied, including as to suitability, fitness for purpose or merchantability and, to the extent permitted by law, accepts no liability for loss or damage arising out of use or reliance on this information.

**HAZARD WARNING:** Avoid creating dust when handling, using or storing the product. Use only with adequate ventilation to keep exposure low. Undertake health and safety risk assessments on safe methods of handling and use appropriate to your workplace. To prevent inhalation of airborne dust, wear respiratory protection in accordance with Australian Standard AS1715 and AS1716. To prevent potential irritation to eyes, wear eye protection in accordance with Australian Standard AS1337.

Please refer to the relevant Terrequip Material Safety Data Sheet (MSDS) for health hazard information before opening or using this product and take care when disposing of the empty bag/container (as it may contain product residue). If you do not have an MSDS, please ring the ACOHS 24 hour emergency phone number 1800 638 556 and you will be sent one.

### FOR PRODUCT INFORMATION AND CUSTOMER SERVICE

**Terrequip:**  
 (61) 07 3871 3837  
 Suite 2B- Ground Floor  
 19 Lang Parade Milton 4064  
 PO Box 1411, Kenmore, QLD, 4129  
 enquiries@terrequip.com  
 sales@terrequip.com

**Warwick Limestone Mine:**  
 (61) 07 4667 9191  
 401 O'Dea's Road, Elbow Valley, QLD, 4370  
 PO Box 1411, Kenmore, QLD, 4129  
 UHF Channel 12  
 warwick@terrequip.com  
 sales@terrequip.com



www.terrequip.com